



XVR-7804EDV 4 Channels H.264 DVR

Pentabrid XVR Compatible with AHD/TVI/CVI/CVBS Cameras



■ Features

4CH 720P/1080N 4 in 1 DVR

Support VGA, HDMI full HD output simultaneously;

Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;

Support web, CMS, center platform management software XMEYE.

Support various mobile monitoring (iPhone, Android);

Remote Access, With DNS (ARSP), easy to monitor remotely

Support UTC, control signal& video stream transmit through one single coaxial

Support AHD/TVI/CVI/CVBS Cameras

■ Full Description

Model		XVR-7804EDV
System	Main processor	Hi3520D V200
Interface	Preview	1CH / 4CH
Video	Codec	H.264
	Monitor quality	VGA,HDMI: HD
	Preview ability	4*1080N
	Encode ability	4*1080N
	Decode ability	1*1080N
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Audio	Audio compression	G.711A
	Intercom	support
Record & playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	4ch(analog input mode)
	Search mode	Search by time, calendar, event, channel
Storage & backup	Video storage	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner

External Interface	Video input	4ch BNC
	Video output	1ch VGA, 1ch HDMI
	Loop Vout	N/A
	Audio I/O	1 Channel Audion In / 1 Channel Audion Out
	Alarm I/O	No
	Network interface	RJ45 10M/100M self-adaption
	PTZ control	No
	USB	2* USB 2.0 ports
	HDD	1*SATA ports (Max 6TB/per)
General	Power supply	12V/3A
	Power Consumption	<15W (without HDD)
	Working environment	Temperature:0℃—+55℃, Humidity:10%—90%, Atm:86kpa—106kpa
	Dimension	250*230*45mm
	Weight	≤2.8 Kg