



CS-1CU

Order No.: 0173060

PRODUCTINFOS

Conference System CS-1

Your opinion will be heard! The control unit CS-1CU, the microphone station for the chairperson CS-1CH and the microphone station for conference delegates CS-1DU together form a conference system with extensive configuration facilities for maximum flexibility.

Control unit, the control centre of the conference system

- For setting up a system with up to 50 microphone stations (2 x 25)
- Power supply for microphone stations
- Built-in speaker
- Headphone connection
- Keypad lock
- Display of date/time
- Stopwatch
- Test function for connected microphone stations
- Connection facilities for optional devices, e.g. external microphone, telephone coupler, signal processing units (e.g. equalizer), recorders, amplifiers, audio line sources

AV-views 02/2010

“A solid and reliable conference system which provides a very clear voice transmission.”

Manufacturer information:

JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.

Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

TECHNICAL SPECIFICATIONS**CS-1CU**

Description	control unit
Suitable for	conference system
Power supply	100-240 V~/50-60 Hz/90 VA
Dimensions	360 x 90 x 150 mm
Weight	1.7 kg

CS-1CU

Connections

- 2 x RCA (input/output for telephone coupler)
- 2 x RCA (input/output, e.g. for equalizer)
- 2 x RCA L/R (input/output for recorder)
- 2 x RCA (input/output for line signals)
- 1 x XLR (microphone input)
- 2 x 7-pole DIN jack (connection for microphone stations)

Packing unit 1

Packaging dimensions (W x H x L) 0.16 x 0.14 x 0.41 m

Gross weight 2.4 kg

Net weight 1.911 kg

CS-1CU

EAN code 4007754212044

Net weight 1.911 kg